



## WATERPROOF CLICK FLOORING



### GENERAL INFORMATION

Classification	ASTM F-3261	Class 1, Type B, Backing Class B
Construction		5.0 mm Core 1.0 mm Attached IXPE Pad 0.5 mm Wear Layer
Plank Size		7.09" x 48.03"
Total Thickness	ASTM F-387	6.0 mm (1/4")
Wear Layer Thickness	ASTM F-410	0.5 mm / 20 mil
Per Carton		8 planks / 18.91 sq.ft
Installation Method		Angle/Angle Locking System

### PERFORMANCE

Critical Radiant Flux	ASTM E-648	Class 1
Chemical Resistance	ASTM F-925	No change in 24 hours
Static Load Limit	ASTM F-970 (mod)	1,000 psi <0.005 in.
Heat Stability	ASTM F-1514	<8.0 Delta E
Light Stability	ASTM F-1515	<8.0 Delta E
Residual Indentation	ASTM F-1914	<0.007 in.
Dimensional Stability	ISO23999	Meets or exceeds F-3261
Coefficient of Friction	ASTM D-2047	Meets or exceeds 0.6
Impact Sound (IIC)	ASTM E-492	IIC 62
Airborne Sound (STC)	ASTM E-90	STC 52
Impact Sound ( $\Delta$ IIC)	ASTM E-2179	$\Delta$ IIC 22

### WARRANTY & CERTIFICATIONS

Warranty	Commercial Manufacturing Residential Manufacturing	15 Years Lifetime
Certifications	Indoor Air Quality (IAQ) Low-Emitting Material Orthophthalates Free Proposition 65 Compliant	  

